TT-554
Remote Probe Sensors



Features & Benefits

- Wide range of sensing element types
- 2m Screened flying lead as standard
- Perfect for tight locations
- Can be used as a duct or immersion sensor

Technical Overview

The TT-554 range of reamote probe temperature sensors are perfect for tight locations, hard to access areas or for applications where the usual duct (TT-D) or immersion (TT-I) sensor will not fit. A 150mm probe is used with either the TT-PO-521 or TT-DFP duct flange plate. Units contain either a high quality thermistor, Platinum or Nickel sensing element. Sensor types compatible with most controls manufacturers' equipment are available.

Specification

Current Output	4 to 20mA
Environmental housing	-10 to +60°C, 0 to 95% RH non-condensing
Environmental media	-30 to +100°C
Gross Weight (kg)	0.1
Lead length	2 meters (5 meter option)
Passive output types	Resistive
Probe dimensions	150 x 6mm
Probe material	Stainless steel
Protection	IP65
Voltage output types	0 to 10Vdc
Weight	125g

Technical Specification

Current Output	4 to 20mA
Weight	125g
Voltage output types	0 to 10Vdc

Tel: +44 (0)1732 861200 | E-mail: sales@sontay.com | Web: www.sontay.com
Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

© 2025 Sontay Limited. All rights reserved. Whilst every effort has been made to ensure the accuracy of this specification, Sontay cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.
Note: for all gas sensors, None of our devices are approved for use in life safety applications. This document is uncontrolled if printed. Generated on 22/07/25

Related Product Codes

TT-554-A	Remote Probe Sensor 10K3A1
-250	Remote Probe Sensor 10K3A1 250MM Probe
5M	Remote Probe Sensor 10K3A1 5M
-65	Remote Probe Sensor 10K3A1 65MM Probe
-LSZH	Remote Probe Sensor 10K3A1 LSZH
TT-554-B	Remote Probe Sensor 10K4A1
TT-554-C	Remote Probe Sensor 20K6A1
TT-554-CVO	Remote Probe Sensor 4-20mA/0-10Vdc
TT-554-CVO-C	Remote Probe Sensor 4-20mA/0-10Vdc
TT-554-D	Remote Probe Sensor PT100A
TT-554-E	Remote Probe Sensor PT1000A
TT-554-F	Remote Probe Sensor Ni1000A
TT-554-G	Remote Probe Sensor LAN1
TT-554-L	Remote Probe Sensor TAC1
TT-554-M	Remote Probe Sensor 2.2K3A1
TT–554–N	Remote Probe Sensor 3K3A1
TT-554-P	Remote Probe Sensor 30K6A1
TT-554-Z	Remote Probe Sensor 10K NTC CAREL

Tel: +44 (0)1732 861200 | E-mail: sales@sontay.com | Web: www.sontay.com

Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

Sontay®

© 2025 Sontay Limited. All rights reserved. Whilst every effort has been made to ensure the accuracy of this specification, Sontay cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

Note: for all gas sensors, None of our devices are approved for use in life safety applications. This document is uncontrolled if printed. Generated on 22/07/25