

Features & Benefits

- Wide range of sensor types
- Choice of output type and temperature ranges on one unit
- Custom output range scaling

Technical Overview

The TT-D are used to measure air temperature in ducts. The sensing element is fitted into a stainless steel probe. A flange plate is available for adjustment of penetration depth (order as TT-DFP).

Specification

Current Output	4 to 20mA
Environmental housing	-30 to +70°C, 0 to 95% RH non-condensing
Environmental media	-10 to +100°C
Gross Weight (kg)	0.13
Housing dimensions	80 x 79 x 44mm
Housing material	PC/GF (Halogen Free Flame Retardant, UV stabilized)
Passive output types	Resistive
Probe dimensions	65, 150 or 250mm x 6mm dia.
Probe material	Stainless steel 304
Protection	IP65
Voltage output types	0 to 10Vdc
Weight	160g

Technical Specification

Housing dimensions	80 x 79 x 44mm
Current Output	4 to 20mA
Weight	160g
Housing material	PC/GF (Halogen Free Flame Retardant, UV stabilized)
Voltage output types	0 to 10Vdc

Tel: +44 (0)1732 861200 | E-mail: sales@sontay.com | Web: www.sontay.com

Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

Sontay®

© 2025 Sontay Limited. All rights reserved. Whilst every effort has been made to ensure the accuracy of this specification, Sontay cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

Note: for all gas sensors, None of our devices are approved for use in life safety applications. This document is uncontrolled if printed. Generated on 22/07/25

Related Product Codes

TT-D-A	Duct Temp Sensor 150MM 10K3A1
-250	Duct Temp Sensor 250MM 10K3A1
TT-D-B	Duct Temp Sensor 150MM 10K4A1
TT-D-C	Duct Temp Sensor 150MM 20K6A1
TT-D-CVO	Duct Air Temp Sensor 4-20mA/0-10Vdc L=150mm
TT-D-CVO-C	Duct Air Temp Sensor 4-20mA/0-10Vdc L=150mm
TT-D-D	Duct Temp Sensor 150MM PT100A
TT-D-E	Duct Temp Sensor 150MM PT1000A
TT-D-F	Duct Temp Sensor 150MM Ni1000A
TT-D-G	Duct Temp Sensor 65MM Ni1000A
TT-D-H	Duct Temp Sensor 150MM SAT1
TT-D-K	Duct Temp Sensor 150MM STA1
TT-D-L	Duct Temp Sensor 150MM TAC1
TT-D-M	Duct Temp Sensor 150MM 2.2K3A1
TT-D-N	Duct Temp Sensor 150MM 3K3A1
TT-D-P	Duct Temp Sensor 150MM 30K6A1
TT-D-Q	Duct Temp Sensor 150MM 50K6A1
TT-D-R	Duct Temp Sensor 150MM 100K6A1
TT-D-S	Duct Temp Sensor 150MM SAT2
TT-D-T	Duct Temp Sensor 150MM SAT3
TT-D-W	Duct Temp Sensor 150MM SIE1
TT-D-Y	Duct Temp Sensor 150MM STA2
-65	Duct Temp Sensor 65MM STA2
TT-D-Z	Duct Temp Sensor 150MM 10K

Tel: +44 (0)1732 861200 | E-mail: sales@sontay.com | Web: www.sontay.com

Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

Sontay®

© 2025 Sontay Limited. All rights reserved. Whilst every effort has been made to ensure the accuracy of this specification, Sontay cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

Note: for all gas sensors, None of our devices are approved for use in life safety applications. This document is uncontrolled if printed. Generated on 22/07/25