

Features & Benefits

- Weatherproof Housing
- Wide range of sensing element types
- Stainless steel probe
- Optional probe lengths, 65, 100,150 & 250mm
- Hinged lid with the facility of tamper proofing

Technical Overview

Immersion sensors are used for measuring the temperature of liquids in pipework. The sensing element is housed in a stainless steel probe fitted to an IP65 rated enclosure, for direct mounting into TT-PO-521 or TT-PO-HP range of stainless steel pockets.

Specification

Current Output	4 to 20mA
Dimensions	80 x 79 x 44mm
Environmental housing	-30 to +70°C, 0 to 95% RH non-condensing
Environmental media	-30 to +100°C
Gross Weight (kg)	0.16
Housing material	PC/GF (Halogen Free Flame Retardant, UV Stabilized)
Passive output types	Resistive
Probe dimensions	65, 150 or 250mm x 6mm dia.
Probe material	Stainless Steel 304
Protection	IP65
Voltage output types	0 to 10Vdc
Weight	160g

Technical Specification

Current Output	4 to 20mA
Weight	160g
Dimensions	80 x 79 x 44mm
Housing material	PC/GF (Halogen Free Flame Retardant, UV Stabilized)
Voltage output types	0 to 10Vdc

Tel: +44 (0)1732 861200 | E-mail: sales@sontay.com | Web: www.sontay.com

Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

Sontay®

© 2025 Sontay Limited. All rights reserved. Whilst every effort has been made to ensure the accuracy of this specification, Sontay cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

Note: for all gas sensors, None of our devices are approved for use in life safety applications. This document is uncontrolled if printed. Generated on 22/07/25

Related Product Codes

-100	TT-I Immersion Sensors 100 mm
-250	TT-I Immersion Sensors 250 mm
-65	TT-I Immersion Sensors 65mm
TT-I-A	Immersion Temp Sensor 150MM 10K3A1
TT-I-B	Immersion Temp Sensor 150MM 10K4A1
TT-I-C	Immersion Temp Sensor 150MM 20K6A1
TT-I-CVO	Immersion Temp Sensor 150MM 0-10V/4-20mA
TT-I-CVO-C	Immersion Temp Sensor 150MM 0-10V/4-20mA Custom
TT-I-D	Immersion Temp Sensor 150MM PT100A
TT-I-E	Immersion Temp Sensor 150MM PT1000A
TT-I-F	Immersion Temp Sensor 150MM Ni1000A
TT-I-G	Immersion Temp Sensor 150MM Ni1000A/TCR
TT-I-H	Immersion Temp Sensor 150MM SAT1
TT-I-L	Immersion Temp Sensor 150MM TAC1
TT-I-M	Immersion Temp Sensor 150MM 2.2K3A1
TT-I-N	Immersion Temp Sensor 150MM 3K3A1
TT-I-P	Immersion Temp Sensor 150MM 30K6A1
TT-I-Q	Immersion Temp Sensor 150MM 50K6A1
TT-I-R	Immersion Temp Sensor 150MM 100K6A1
TT-I-S	Immersion Temp Sensor 150MM SAT2
TT-I-T	Immersion Temp Sensor 150MM SAT3
TT-I-W	Immersion Temp Sensor 150MM SIE1
TT-I-Y	Immersion Temp Sensor 150MM STA2
TT-I-Z	Immersion Temp Sensor 150MM 10K

Tel: +44 (0)1732 861200 | E-mail: sales@sontay.com | Web: www.sontay.com

Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

Sontay®

© 2025 Sontay Limited. All rights reserved. Whilst every effort has been made to ensure the accuracy of this specification, Sontay cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

Note: for all gas sensors, None of our devices are approved for use in life safety applications. This document is uncontrolled if printed. Generated on 22/07/25